


Spaltband

Aluminiumlegierungen



Dicke in mm	Kg/m ² ca.	EN AW-1050A Al99,5			EN AW-5005A AlMg1	EN AW-5754 AlMg3		
		0 / H111	H14/24	H19/26	H24	0 / H111	H22	H26
0,20	0,54	□	●	□	□	□	●	□
0,30	0,81	●	●	●	□	●	●	□
0,40	1,08	●	●	●	□	●	●	□
0,50	1,35	●	●	●	●	●	●	●
0,60	1,62	●	●	●	●	●	●	●
0,70	1,89	●	●	●	□	●	●	●
0,80	2,16	●	●	●	●	●	●	●
1,00	2,70	●	●	□	●	●	●	●
1,20	3,24	●	●	□	●	●	●	●
1,25	3,38	●	●	●	●	●	●	●
1,30	3,51	□	●	□	□	□	□	□
1,50	4,05	●	●	●	●	●	●	●
2,00	5,40	●	●	□	●	●	●	●
2,50	6,75	●	●	□	●	●	●	□
3,00	8,10	●	●	□	●	●	●	□
3,50	9,45	□	□	□	□	□	●	□
4,00	10,80	□	□	□	□	□	●	□
5,00	13,50	□	□	□	□	□	●	□

- aus Vorrat
- Neuproduktion

Breite: 5,0 – 2000 mm

Ringinnendurchmesser: 400 + 500 / 508 mm

Sprechen Sie uns an: +49(0)2058 8989383 sales@metallhaus.eu