

## Sechskantstangen

### Aluminiumlegierungen

gezogen · gepresst



Schlüsselweite in mm	Kg/m ca.	EN AW-2007 AlCu4PbMgMn T4	EN AW-2011 AlCu6BiPb T3	EN AW-6012 AlMgSiPb T6	EN AW-6082 AlSi1MgMn T6
5,0	0,06	•	•	•	
6,0	0,08	•	•	•	
7,0	0,11	•	•		•
8,0	0,15	•	•	•	
9,0	0,19	•	•		•
10,0	0,23	•	•	•	•
11,0	0,28	•	•	•	•
12,0	0,34	•	•	•	•
13,0	0,39	•	•	•	•
14,0	0,46	•		•	•
15,0	0,52	•	•	•	
16,0	0,60	•		•	
17,0	0,67	•	•	•	•
19,0	0,84	•		•	•
20,0	0,93	•			
21,0	1,03	•			
22,0	1,13	•		•	•
24,0	1,34	•		•	•
27,0	1,70	•		•	•
28,0	1,83	•			
29,0	1,96	•			
30,0	2,10	•			•
32,0	2,38	•		•	•
36,0	3,02	•		•	•
41,0	3,91	•		•	•
46,0	4,93	•		•	
50,0	5,82	•			•
55,0	7,04	•			
60,0	8,38	•			
65,0	9,84	•			
70,0	11,41	•			
80,0	14,90	•			