

Vierkantrohre

CuZn37 CW508L H115 / R440 (hart)



nahtlos gezogen · Herstelllängen ca. 5 m

Abmessung in mm	Kg/m ca.	Abmessung in mm	Kg/m ca.
6 x 6 x 1,0	0,17	25 x 25 x 2,0	1,56
7 x 7 x 1,0	0,20	28 x 28 x 1,0	0,92
8 x 8 x 1,0	0,24	30 x 30 x 1,0	0,99
9 x 9 x 1,0	0,27	30 x 30 x 1,5	1,45
10 x 10 x 1,0	0,31	30 x 30 x 2,0	1,90
11 x 11 x 1,0	0,34	32 x 32 x 1,0	1,05
12 x 12 x 1,0	0,37	35 x 35 x 1,0	1,16
13 x 13 x 1,0	0,41	35 x 35 x 1,5	1,71
14 x 14 x 1,0	0,44	35 x 35 x 2,0	2,24
15 x 15 x 1,0	0,48	40 x 40 x 1,0	1,33
15 x 15 x 1,5	0,69	40 x 40 x 1,5	1,96
16 x 16 x 1,0	0,51	40 x 40 x 2,0	2,58
17 x 17 x 1,0	0,54	45 x 45 x 1,0	1,50
18 x 18 x 1,0	0,58	45 x 45 x 1,5	2,22
20 x 20 x 1,0	0,65	45 x 45 x 2,0	2,92
20 x 20 x 1,5	0,94	50 x 50 x 1,0	1,67
25 x 25 x 2,0	1,56	50 x 50 x 1,5	2,47
22 x 22 x 1,0	0,71	50 x 50 x 2,0	3,26
25 x 25 x 1,0	0,82	60 x 60 x 1,35	2,69
25 x 25 x 1,5	1,20	80 x 80 x 2,0	5,30

Sprechen Sie uns an: +49(0)2058 8989383 sales@metallhaus.eu