

Sechskantstangen

CuZn39Pb3 CW614N

gezogen · gepresst



Schlüsselweite in mm	Kg/m ca.	Schlüsselweite in mm	Kg/m ca.
2,5	0,05	27,0	5,34
3,0	0,07	28,0	5,75
3,5	0,09	29,0	6,17
4,0	0,12	30,0	6,60
4,5	0,15	32,0	7,51
5,0	0,18	33,0	7,98
5,5	0,22	34,0	8,47
6,0	0,26	35,0	8,98
6,5	0,31	36,0	9,50
7,0	0,36	38,0	10,59
8,0	0,47	40,0	11,73
9,0	0,59	41,0	12,32
10,0	0,73	42,0	12,93
11,0	0,89	43,0	13,56
12,0	1,06	44,0	14,19
13,0	1,24	46,0	15,51
14,0	1,44	48,0	16,89
15,0	1,65	50,0	18,33
16,0	1,88	55,0	22,18
17,0	2,12	60,0	26,39
18,0	2,38	65,0	30,97
19,0	2,65	70,0	35,92
20,0	2,93	75,0	41,24
21,0	3,23	80,0	46,92
22,0	3,55	85,0	52,97
23,0	3,88	90,0	59,38
24,0	4,22	100,0	73,31
25,0	4,58	110,0	88,71
26,0	4,96		

Sprechen Sie uns an: +49(0)2058 8989383 sales@metallhaus.eu